



428 ASJ

All Service Jacket – UL® 723 Rated

Description

428AWF is a pressure sensitive tape manufactured with the ASJ Foil / Scrim / Kraft facing used by most major manufacturers of ASJ faced insulation.

Applications

- Used for sealing cold and dual temperature duct and pipe systems where the basic insulation uses ASJ facing.
- Pre-cut discs (428D) are applied over washers and cupped pin heads or to repair any accidental punctures in the facing.

Features and Benefits

- Performance All Weather Formula adhesive system provides permanent bond to ASJ insulation facing
- Laminated foil / scrim / kraft backing offers conformability, strength and a high quality appearance.
- Release liner provides easy removal for efficient application on the job site
- Available pre-cut discs reduce on site labor and provide an excellent vapor seal. For best results please use the provided applicator

<u>Physical Properties:</u>	<u>US Measurements</u>	<u>Metric</u>
Backing Type	ASJ (All Service Jacket)	ASJ (All Service Jacket)
Adhesion to Steel	73.0 (oz./in. width)	20.30 n/25.4 mm.
Adhesive System	Acrylic	Acrylic
Tensile	50.0 (lbs./in. width)	222.36 n/25.4 mm.
Thickness	11.0 mils	0.28 mm.
Elongation	3.0%	3.0%
Application Temp. Range	-25° F to 280° F	-31.67° C to 137.78° C
Post Application Temp. Range	-25° F to 280° F	-31.67° C to 137.78° C
UL 723 Ratings	Flame Spread 5 Smoke Developed 0	Flame Spread 5 Smoke Developed 0

NOTE: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry, and free of grease, oil or other contaminants.

ITC – 7/2009

METRO SUPPLY COMPANY

12 Andrews Drive
Woodland Park, NJ 07424

Telephone: 973-237-1551

Fax: 973-237-1552

Internet: www.metrosupplycompany.com

Email: info@metro-supply-co.com