



## Sound SealR Acoustic Sound Blocking Sealant

MetroFlex Sound SealR Acoustic Sound Blocking Sealant is a high quality latex-based sealing compound used as an essential component in construction assemblies for achieving and maintaining the required STC rating as per IBC 1207.2 for air-borne sound. Sound SealR is specifically formulated for use with MetroFlex Mass Loaded Vinyl and possesses excellent adhesion to drywall, wood, metal, and concrete. It remains permanently flexible and is both durable and long lasting.

### Applications:

- Joint seams of Mass Loaded Vinyl
- Top and bottom runners prior to installation of drywall
- Outer edge perimeter joints of drywall
- Cut-outs and utility penetrations

### Acoustical Properties\*

MetroFlex Sound Barrier provides the following noise reduction.

#### Noise transmission loss (dB)/Frequency (Hz)

Hz	125	250	500	1000	2000	4000	STC
<b>db by density:</b>							
MF-05	8	13	17	22	27	31	20
MF-10	16	17	22	27	31	36	26
MF-15	17	19	25	31	36	44	29
MF-20	16	22	26	32	35	40	31

Tensile Strength	2,750 KPa (400 psi)
------------------	---------------------

Tear Strength	12.5 Kg/cm (70 lbs./in.)
---------------	--------------------------

Thickness	.100"
-----------	-------

Ultimate Elongation	200%
---------------------	------

Flammability	SE "O" in/min.
--------------	----------------

Temperature Range	-40°F to 180°F
-------------------	----------------



### Product Features

Maintains 52 STC  
 Tested to ASTM-E90  
 Meets ASTM-C834  
 Permanently Flexible  
 Excellent Adhesion  
 Paintable  
 Low V.O.C (11 g/l)



#### METRO SUPPLY COMPANY

12 Andrews Drive  
 Woodland Park, NJ 07424

Telephone: 973-237-1551

Fax: 973-237-1552

Internet: [www.metrosupplycompany.com](http://www.metrosupplycompany.com)

Email: [info@metro-supply-co.com](mailto:info@metro-supply-co.com)

**- Don't let your soundproofing project fall through the Cracks -**